

## Thermo Scientific Sulfur Dioxide Analyzer, Model 43i

Pulsed fluorescence gas analyzer



The Thermo Scientific Sulfur Dioxide (SO<sub>2</sub>) Analyzer, Model 43i utilizes pulsed fluorescence technology to measure the amount of sulfur dioxide in the air up to 100 ppm.

The pulsing of the U.V. source lamp serves to increase the optical intensity whereby a greater U.V. energy throughput and lower detectable SO<sub>2</sub> concentration are realized.

Reflective bandpass filters, as compared to commonly used transmission filters, are less subject to photochemical degradation and more selective in wavelength isolation. This results in both increased detection specificity and long term stability.

This state-of-the-art gas analyzer offers features such as an Ethernet port as well as flash memory for increased data storage.

Ethernet connectivity provides efficient remote access, allowing the user to download measurement information directly from the instrument without having to be on-site.

You can easily program short-cut keys to allow you to jump directly to frequently accessed functions, menus or screens. The larger interface screen can display up to five lines of measurement information while primary screen remains visible.

### Key Features

- Approved to meet the following standards: US EPA, UK Environmental Agency and the European Union
- Ethernet connectivity for efficient remote access
- Enhanced user interface with one button programming and large display screen
- Flash memory for increased data storage and user downloadable software
- Enhanced electronics design optimizes product commonality

# Product Specifications

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

## Sulfur Dioxide Analyzer, Model 43i

<b>Preset Ranges</b>	0-0.05, 0.1, 0.2, 0.5, 1, 2, 5, and 10 ppm 0-0.2, 0.5, 1, 2, 5, 10, 20, and 25 mg/m <sup>3</sup>
<b>Extended Ranges</b>	0-0.05, 1, 2, 5, 10, 20, 50 and 100 ppm 0-2, 5, 10, 20, 50, 100, 200, and 250 mg/m <sup>3</sup>
<b>Custom Ranges</b>	0-0.05 to 100 ppm 0-0.2 to 250 mg/m <sup>3</sup>
<b>Zero Noise</b>	1.0 ppb RMS (10 second averaging time), 0.5 ppb RMS (60 second averaging time), 0.25 ppb RMS (300 second averaging time)
<b>Lower Detectable Limit</b>	2.0 ppb (10 second averaging time), 1.0 ppb (60 second averaging time), 0.5 ppb (300 second averaging time)
<b>Zero Drift (24 hour)</b>	Less than 1 ppb
<b>Span Drift (24 hour)</b>	+/-0.5%
<b>Response Time</b>	80 seconds (10 second average time) 110 seconds (60 second average time) 320 seconds (300 second average time)
<b>Precision</b>	1% of reading or 1 ppb (whichever is greater)
<b>Linearity</b>	+/-1% full scale < 100ppm
<b>Sample Flow Rate</b>	0.5 liters/min. (standard) 1 liter/min. (optional)
<b>Interferences (EPA levels)</b>	< lower detectable limit except for the following: NO < 3 ppb, M-Xylene < 2 ppb, H <sub>2</sub> O < 2% of reading
<b>Operating Temperature</b>	20 <sup>o</sup> C - 30 <sup>o</sup> C
<b>Power Requirements</b>	100 VAC, 115 VAC, 220-240 VAC +/-10% @ 165W
<b>Size and Weight</b>	16.75"(W) x 8.62"(H) x 23"(D), 48 lbs. (21.8 kg)
<b>Outputs</b>	Selectable Voltage, RS232/RS485, TCP/IP, 10 Status Relays, and Power Fail Indication (standard). 0-20 or 4-20 mA Isolated Current Output (optional)
<b>Inputs</b>	16 Digital Inputs (standard), 8 0-10Vdc Analog Inputs (optional)
<b>Approvals and Certifications</b>	US EPA Equivalent Method: EQSA-0486-060 MCERTS Certified: Sira MC070094/00 EN14212: TÜV 936/21203248/D Report

## Ordering Information

### Sulfur Dioxide Analyzer, Model 43i

Choose from the following configurations/options to customize your own Model 43i

#### 1. Voltage options:

A = 120 VAC 50/60 Hz (standard)  
B = 220 VAC 50/60 Hz  
J = 100 VAC 50/60 Hz

#### 2. Internal zero / span and/or Oxygen Sensor:

N = No zero / span assembly (standard)  
Z = Internal zero span assembly  
P = Internal permeation span source w/ zero/span assembly  
L = Oxygen Sensor with No Zero/Span  
K = Oxygen Sensor with Zero/Span

#### 3. Kicker Type:

S = Standard  
H = Heated

#### 4. Optional I/O:

A = None (standard)  
C = 0-20, 4-20mA current output - 6 channels,  
0-10v analog input - 8 channel

#### 5. Mounting Hardware:

A = Bench mounting (standard)  
B = Ears & handles, EIA  
C = Ears & handles, retrofit

**Your Order Code: 43i -** \_ \_ \_ \_ \_

Lit\_43iAQI\_3/10

© 2010 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries.

This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. Not all products are available in all countries. Please consult your local sales representative for details.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

#### Air Quality Instruments

27 Forge Parkway  
Franklin, MA 02038 USA

(866) 282-0430  
(508) 520-0430  
(508) 520-1460 fax

[www.thermo.com/air](http://www.thermo.com/air)

**Thermo**  
SCIENTIFIC