

Full Extractive Probe, Model PRO3000

Modular, external probe for wet or dry-basis measurement



The Thermo Scientific Model PRO3000 probe utilizes full extractive technology for wet or dry-basis measurement.

The PRO3000 full extractive probe assembly extracts the sample through a heated probe barrel and filters out sub-micron particles using the heated filter. Periodic blowbacks keep the filter clean and operating properly. The probe is designed so no tools are required to change the filter element.

The temperature of the probe barrel and filter may be controlled by either an optional PRO3000 controller or the iMEGA CEMS probe controller.

Housed in a NEMA 4X enclosure to protect from harsh environments, this probe is highly durable and easily mountable to the stack or duct.

The PRO3000 probe assembly includes a full extractive probe, a heated probe barrel, a purge valve, a check valve and an insulated enclosure.

This probe passes calibration gas through the filter element in compliance with US EPA requirements as defined in 40CFR Part 75 and 40CFR Part 60 for continuous emissions monitoring using extractive technology.

Typical applications include:

- Utility boilers
- Pulp and paper mills
- Waste to energy facilities
- Incinerators
- Turbines
- Refineries
- Petrochemical
- Cogeneration facilities

Key Features

- NEMA 4X Fiberglass enclosure for protection from harsh stack environments
- Low maintenance, reusable ceramic filter
- Versatile design for a wide range of applications
- Complies with US EPA requirements as defined in 40CFR Part 60


Full Extractive Probe, Model PRO3000

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product lifecycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

Product Specifications

Power Requirements	120VAC, 310 Watts or 240VAC, 1310 Watts with heated probe barrel
Ambient Operating Temperature Range	-4 °F to +122°F (-20°C to +50°C)
Maximum Process Temperature	1,112 °F (600 °C)
Instrument Air Required for Purge	Clean Dry Air at -40°F (-40°C) dew point, 60 PSI minimum
Size and Weight	17" (43.2cm) W x 19" (48.3cm) H x 10.5" (26.7cm) D, 39lbs (17.7 kgs) 52.5lbs. (23.8 Kg) with heated probe barrel
Probe Barrel	5/8" Thick wall, 316 Stainless steel tubing
<i>Length</i>	52" (132cm)
Heated Filter	0.1 Micron glass fiber element
<i>Temperature</i>	290°F (143.3°C)
Remote Electronic Control	Single loop controllers for temperature control +/-2°F (1.1°C)
Materials of Construction	
Enclosure	NEMA 4X Fiberglass - 18" (45.7cm) H x 16" (40.6cm) W x 10" (25.4cm) D
Filter Body	316 Stainless Steel, temperature controlled at 290°F (143.3°C)
Options	
Probe Barrel	Teflon-lined 316 Stainless steel (applications below 275°F), Hastelloy C-276, other, specify
Mounting Flange	Size other than 4", specify
Heated Filter	Special Materials for reactive gases (HCl, NH ₃ , THC, etc.)
Enclosure	Other, specify
Non-insulated Stack	Enclosure cooling, A/C or vortex cooler

Simplified Probe Assembly



This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary.
© 2009 Thermo Fisher Scientific, Inc. All rights reserved Thermo Fisher Scientific, Inc.

**Environmental
Instruments Division**
Air Quality Instruments

27 Forge Parkway
Franklin, MA 02038
(866) 282-0430 (Toll Free)
(508) 520-1460 fax

45 Fir Street
Waldron, AR 72958
(479) 637- 4152
(479) 637- 2687 (Fax)

www.thermo.com/air

Lit_PRO3000AQI_01/09

Thermo
SCIENTIFIC